

Fujikura 22S

NEW

The Advanced FTTH Splicer

**Active
V-groove
Alignment**



Single Fiber Fusion Splicer

Fujikura 22S *Active V-groove Alignment*



- Excellent for FTTH
- World's Smallest & Lightest Active V-groove Splicer
- Fast splicing time 9sec.
- Multi-Functional Carrying Case



 **Fujikura**

Fujikura 22S

SPECIFICATIONS

Applicable fibers	Single / SMF(G.652/657), MMF(G.651), DSF(G.653), NZDSF(G.655)
Cladding dia. / Sheath dia.	125 µm / Up to 3mm with sheath clamp
Cleave length	5mm to 16mm
Splice mode / heating mode	Total 100 splice modes / 30 heating modes
Typical splice loss	0.03dB (SM), 0.01dB(MM), 0.05dB(DS) and 0.05dB(NZDS) Measured by cut-back method relevant to ITU-T and IEC standards.
Splice time	Typical 9sec SM FAST, Typical 11sec SM AUTO
Tube heating time	Typical 24sec FP-03, coating dia.250µm Typical 25sec FP-03, coating dia.900µm Typical 19sec Slim60mm, coating dia.250µm Typical 16sec Slim40mm, coating dia.250µm
Splice result storage	Last 10,000 splices
Viewing methods / magnification	2 axis 2CMOS camera with 4.73" color LCD. 132X magnification.200X magnification after splicing
Tension test	1.96 to 2.25N
Applicable protection sleeve	60mm, 40mm and Fujikura micro sleeves
No. of splice / heating per battery full charge	Typical 200 cycles with BTR-11
Electrode life	5000 splices
Size / weight	120W x 189D x 72H mm / 1140g (including battery)
Operating condition	Altitude : 0 to 5,000m above sea level, Wind : 15m/sec Temperature : -10 to 50deg C, Humidity : 0 to 95%RH, non-dew
Other features	PC software upgrade / data management
Resistance feature	Shock resistance : 76cm (30inch) bottom surface drop ^{*1} Dust resistance : Exposure to dust (0.1 to 500µm dia. Alumina Silicate). ^{*1} Rain resistance : H=10mm/hr for 10min ^{*1}

*1:Carried out in Fujikura labs in Japan. The shock resistance, dust resistance and rain resistance test do not guarantee that the product will not be damaged under these conditions.

STANDARD PACKAGE

Description	Model No.	Q'ty
Fusion splicer	22S with BTR-11 and ELCT2-12	1pc
AC adapter	ADC-19	1pc
AC power cord	ACC-XX XX=08(JP),09(US),10(UK),11(EU),12(AU)	1pc
Carrying case	CC-32	1pc
Spare electrodes	ELCT2-12	1pair
Instruction manual CD	M-22	1pc
Quick reference guide	Q-22S-E	1pc
Alcohol pot	AP-01	1pc
Screw driver	SD-01	1pc

OPTIONAL ITEMS


Description	Model No.
Fiber holder	FH-60-250 (coating dia. of 250µm)
	FH-60-900 (coating dia. of 900µm)
	FH-60-DC250 (coating dia. of 250µm in drop cable)
	FH-FC-20 (coating dia. of 900µm in 2.0mm Sheath dia.)
	FH-FC-30 (coating dia. of 900µm in 3.0mm Sheath dia.)
Sheath clamp	CLAMP-S21A (included in standard package)
	CLAMP-S21B (900µm dia. loose buffer fiber)
Battery pack	BTR-11(Li-ion) ^{*2}
Electrodes	ELCT2-12

*2:all senders have to ovey the IATA regulation in case of Li-ion battery transportation by air.

ACCESSORIES

Description	Model No.
High precision single fiber cleaver	CT-06 (for single fiber)
High precision fiber cleaver	CT-30 series (for single to 12 ribbon fibers)
Primary coat stripper	PS-02
Nylon jacket stripper	JS-01
Protection sleeve	FP-03 / 03 (L=40) and FPS01series

STANDARD PACKAGE



OPTIONAL ITEMS



For quotations and product demonstrations:

FinishAdapt Ltd

Unit 8 Hillmead Industrial Estate
Marshall Road
Swindon
SN5 5FZ
UK

Email: sales@finishadapt.com

Tel: +44 (0)1793 758720

Fax: +44 (0)1793 876059

www.finishadapt.com