



Part Number	Fiber Size	Nominal Product Dimensions mm			Strength Member mm		
		Recovered Diameter	Product Length	Supplied Bore id	Pin Diameter	Pin Length	Pin Material
MICRO SLEEVE SERIES – SINGLE FIBER:							
PS-6A-X10U	250µm	1.3	10	0.35	0.5	10	Stainless Steel
PS-6A-X12U	250µm	1.3	12	0.35	0.5	12	Stainless Steel
PS-6A-X15U	250µm	1.3	15	0.35	0.5	15	Stainless Steel
PS-6A-X20U	250µm	1.3	20	0.35	0.5	20	Stainless Steel
PS-6A-X25U	250µm	1.3	25	0.35	0.5	25	Stainless Steel
PS-6A-X30U	250µm	1.3	30	0.35	0.5	30	Stainless Steel
PS-6A-X40U	250µm	1.3	40	0.35	0.5	40	Stainless Steel
PS-SP-059 (clamshell Equiv)*	250µm	1.26	30	0.35	0.5	30	Stainless Steel
MINI SLEEVE SERIES – SINGLE FIBER:							
PS-6A-X25PS	250µm	1.6	25	0.35	0.8	25	Stainless Steel
PS-6A-X30PS	250µm	1.6	30	0.35	0.8	30	Stainless Steel
PS-6A-X40PS	250µm	1.6	40	0.35	0.8	40	Stainless Steel
MIDI SLEEVE SERIES – SINGLE FIBER:							
PS-6A-X15M	250-900 µm	1.9	15	1.3	0.5	15	Stainless Steel
PS-6A-X20M	250-900 µm	1.9	20	1.3	0.5	20	Stainless Steel
PS-6A-X25M	250-900 µm	1.9	25	1.3	0.5	25	Stainless Steel
PS-6A-X30M	250-900 µm	1.9	30	1.3	0.5	30	Stainless Steel
PS-6A-X40M	250-900 µm	1.9	40	1.3	0.5	40	Stainless Steel
5A STANDARD SLEEVE SERIES – SINGLE FIBER:							
PS-5A-X35	250-900 µm	2.1	35	1.2	0.8	31	Stainless Steel
PS-5A-X45	250-900 µm	2.1	45	1.2	0.8	40	Stainless Steel
PS-5A-X	250-900 µm	2.1	61	1.2	0.8	57	Stainless Steel
PS-5A-X45/Y (Yellow tint)	250-900 µm	2.1	45	1.2	0.8	40	Stainless Steel
3A STANDARD SLEEVE SERIES – SINGLE FIBER – CLEAR & 10 COLOURS:							
PS-3A-X22	250-900 µm	2.4	22	1.4	1.0	18	Stainless Steel
PS-3A-X25	250-900 µm	2.4	25	1.4	1.0	21	Stainless Steel
PS-3A-X30	250-900 µm	2.4	30	1.4	1.0	27	Stainless Steel
PS-3A-X35	250-900 µm	2.4	35	1.4	1.0	31	Stainless Steel
PS-3A-X40	250-900 µm	2.4	40	1.4	1.0	36	Stainless Steel
PS-3A-X45	250-900 µm	2.4	45	1.4	1.0	41	Stainless Steel
PS-3A-X50	250-900 µm	2.4	50	1.4	1.0	46	Stainless Steel
PS-3A-X	250-900 µm	2.4	61	1.4	1.0	57	Stainless Steel
US SLEEVE SERIES – SINGLE FIBER:							
PS-3A-X23/US	250-900 µm	2.6	23	1.4	1.4	19	Stainless Steel
PS-3A-X40/US	250-900 µm	2.6	40	1.4	1.4	36	Stainless Steel
PS-3A-X45/US	250-900 µm	2.6	45	1.4	1.4	41	Stainless Steel
PS-3A-X/US	250-900 µm	2.6	61	1.4	1.4	57	Stainless Steel
US LARGE SLEEVE SERIES – SINGLE FIBER:							
PS-3A-X40/USL	250-900 µm	2.9	40	1.4	1.5	36	Stainless Steel
PS-3A-X45/USL	250-900 µm	2.9	45	1.4	1.5	40	Stainless Steel
PS-3A-X/USL	250-900 µm	2.9	61	1.4	1.5	55	Stainless Steel

All product available in Clear. 3A Standard series also available in 10 colours

* PS-SP-059 is a replacement fusion splice protector sleeve for fold-over clamshell/butterfly types

Our most popular products are shown in Red

Custom products can be designed and manufactured to customer's requirements



Part Number	Fiber Size	Nominal Product Dimensions mm			Strength Member mm		
		Recovered Diameter	Product Length	Supplied Bore id	Pin Diameter	Pin Length	Pin Material
1A LARGE SLEEVE SERIES – SINGLE FIBER:							
PS-1A-X40S	250-900 µm	3.0	40	1.9	1.4	36	Stainless Steel
PS-1A-X40	250-900 µm	3.2	40	1.9	1.6	36	Stainless Steel
PS-1A-X45	250-900 µm	3.2	45	1.9	1.6	41	Stainless Steel
PS-1A-X	250-900 µm	3.2	61	1.9	1.6	57	Stainless Steel
2A EXTRA LARGE SLEEVE SERIES – SINGLE FIBER:							
PS-2A-X	250-900 µm	3.7	68	1.9	1.6	57	Stainless Steel
1-8 WAY RIBBON SLEEVE SERIES – MULTIPLE (MASS) FIBER:							
PS-94-X30C	1-8 Ribbon	2.8-3.7	30	3.0 x 1.0	3.0 x 1.0	30	White Ceramic
PS-94-X40C	1-8 Ribbon	2.8-3.7	40	3.0 x 1.0	3.0 x 1.0	40	White Ceramic
1-12 WAY RIBBON SLEEVE SERIES – MULTIPLE (MASS) FIBER:							
PS-99-X25C	1-12 Ribbon	3.75-4.75	25	3.5 x 1.0	3.9 x 1.85	25	White Ceramic
PS-99-X30C	1-12 Ribbon	3.75-4.75	30	3.5 x 1.0	3.9 x 1.85	30	White Ceramic
PS-99-X40C	1-12 Ribbon	3.75-4.75	40	3.5 x 1.0	3.9 x 1.85	40	White Ceramic
NON METALLIC PIN – DIELECTRIC SLEEVE SERIES – SINGLE FIBER:							
PS-3D-X30	250-900 µm	2.4	30	1.4	1.0	27	FRP Rod
PS-3D-X40	250-900 µm	2.4	40	1.4	1.0	36	FRP Rod
PS-3D-X45	250-900 µm	2.4	45	1.4	1.0	41	FRP Rod
PS-3D-X	250-900 µm	2.4	61	1.4	1.0	57	FRP Rod
FLEXIBLE 6A MICRO / MINI SLEEVE SERIES – SINGLE FIBER:							
PS-6A-X15UNP	250µm	1.1	15	0.35	No Strength Member		
PS-6A-X25UNP	250µm	1.1	25	0.35	No Strength Member		
PS-6A-X25NP	250µm	1.45	25	0.35	No Strength Member		
PS-6A-X40NP	250µm	1.45	40	0.35	No Strength Member		
PS-SP-154	250-400µm	1.45	30	0.60	No Strength Member		
FLEXIBLE 3A STANDARD SLEEVE SERIES – SINGLE FIBER:							
PS-3A-X18NP	250-900 µm	2.1	18	1.4	No Strength Member		
PS-3A-X20NP	250-900 µm	2.1	20	1.4	No Strength Member		
PS-3A-X25NP	250-900 µm	2.1	25	1.4	No Strength Member		
PS-3A-X40NP	250-900 µm	2.1	40	1.4	No Strength Member		
PS-3A-X45NP	250-900 µm	2.1	45	1.4	No Strength Member		
PS-3A-XNP	250-900 µm	2.1	61	1.4	No Strength Member		
PS-3A-X90NP	250-900 µm	2.1	90	1.4	No Strength Member		

All product available in Clear. 3A Standard series also available in 10 colours

* PS-SP-059 is a replacement fusion splice protector sleeve for fold-over clamshell/butterfly types

Our most popular products are shown in Red

Custom products can be designed and manufactured to customer's requirements

Technical Data Sheets available at www.finishadapt.com Contact us for further details: sales@finishadapt.com