

## Splice Protector Sleeve – Selection Guide

Design Criteria	<u>059</u>	<u>6A-U Series</u>	<u>6A-PS Series</u>	<u>6A-M Series</u>	<u>5A Series</u>	<u>3A Series</u>	<u>3A US Series</u>	<u>3A USL Series</u>	<u>1A Series</u>	<u>2A Series</u>	<u>6A-UNP Series</u>	<u>6A-NP Series</u>	<u>154</u>	<u>3A-NP Series</u>	<u>3D Series</u>	<u>94</u>	<u>99</u>
Single Fiber	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
Ribbon Fiber																✓	✓
250um	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		
900um				✓	✓	✓	✓	✓	✓	✓				✓	✓		
Flexible - Pinless											✓	✓	✓	✓			
Non-Metallic Pin															✓		
Stainless Steel Pin	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓							
Ceramic Pin																✓	✓
1.1 mm diameter											✓						
1.26 mm diameter	✓																
1.3 mm diameter		✓															
1.45 mm diameter												✓	✓				
1.6 mm diameter			✓														
1.9 mm diameter				✓													
2.1 mm diameter					✓										✓		
2.4 mm diameter						✓									✓		
2.6 mm diameter							✓										
2.9 mm diameter								✓									
3.2 mm diameter									✓								
3.7 mm diameter										✓							
1 to 8 way Ribbon																✓	
1 to 12 way Ribbon																	✓
Clear	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Coloured						✓											✓

Please refer to the Technical Data Sheets for full product information. The 'diameter' refers to outside diameter when fully shrunk in a fusion splicer oven.

[sales@finishadapt.com](mailto:sales@finishadapt.com)

<https://finishadapt.com/>